



FIBER-PATCH

PRODUCT

CAFECO® FIBER-PATCH is a versatile, hand-applied fire resistive material designed for patching damaged CAFECO Dry Mix and Wet Mix Spray-Applied Fire Resistive Materials (SFRMs). FIBER-PATCH is easy to use and requires no special equipment. For small areas, it can be easily mixed in a 5 gallon (19 liter) bucket and applied by hand or trowel.

FIBER-PATCH has excellent bonding characteristics and easily adheres to steel surfaces and the material being patched. When patching Dry Mix SFRMs, individual patches are limited to 3 ft² (0.3 m²). Individual patch areas for Wet Mix SFRMs are limited to 1 ft² (0.1 m²). For complete instructions, please refer to the FIBER-PATCH Short Form Application Guide.

FEATURES

- UL Classified
- Asbestos Free
- Single Component Mix
- Direct Hand Application
- Economical and Easy to Apply



FIRE RESISTANCE RATINGS

CAFECO FIBER-PATCH has been tested by Underwriters Laboratories, Inc. (UL) for fire endurance in accordance with ASTM E119 (UL 263). FIBER-PATCH is classified for use in most UL designs.

Physical Performance

Characteristic	ASTM Method	Values*
Density	E605	22 pcf (352 kg/m ³)
Cohesion/Adhesion	E736	150 psf (7.2 kPa)
Compressive Strength	E761	750 psf (35.9 kPa)
Air Erosion Resistance	E859	Less than 0.025 g/ft ² (0.27 g/m ²)
Combustibility	E1354	Noncombustible
Coverage		13 Bd. Ft./Bag (30 m ² @ 1mm)

* Values represent typical standard performance when applied in accordance with written application instructions.

FURTHER INFORMATION

CAFECO Technical and Sales Representatives are always available to lend assistance. Additional printed materials, including Material Safety Data Sheets, and other product literature, are available upon request. For more information about our CAFECO line of sprayed fire protection, thermal and acoustical treatments, SprayFilm™ intumescent coatings and CAFECO-BOARD™ rigid board fire protection or for the name of the Sales Representative in your area, please contact:

In the United States: Isolatek International, Stanhope, New Jersey Tel: 800.631.9600 Fax: 973.347.9170

In Mexico & Central America: Cafco Mexico S.A. de C.V., Mexico D.F. Tel: 525.254.6683 Fax: 525.531.7826

In Andean Countries: Cafco Andina S.A., Santiago, Chile Tel: 562.378.5120 Fax: 562.378.5121

In Canada: Cafco Industries, Etobicoke (Ontario) Tel: 888.873.0003 Fax: 416.679.2933

Visit our website at www.cafco.com

or e-mail us at cafco@isolatek.com

ISOLATEK
INTERNATIONAL

© ISOLATEK International MMI
All Rights Reserved
Printed in the U.S.A. 5K August 2001

The performance data herein reflect our expectations based on tests conducted in accordance with recognized standard methods under controlled conditions. The sale of these products shall be subject to the Terms and Conditions of Sale set forth in the Company's invoices. No agent, employee or representative of the Company, or its subsidiary or affiliated companies, is authorized to modify this statement.



Total Passive Fire Protection